HERESTRONG HS28

2.8-tonne mini excavator with A/C cab



Net price

€18,890

+ VAT · VAT invoice PL / EU
24-month warranty
Service and parts in Poland
AVELTRACK GPS included

2.8-tonne mini excavator with a Kubota D1105 Stage V engine. Standard enclosed cab with air conditioning, radio and suspension seat, Le-HydrauliX piston pump, pilot controls, two-speed travel and boom swing.

Technical data

Operating weight	**2,800 kg**
Engine	**KUBOTA D1105**
Power	**15.7 kW**
Emissions	**EU Stage V**
Cab / protection	**enclosed, A/C, radio, suspension seat**
Air conditioning	**standard**
Max. digging depth	**2,500 mm**
Max. digging height	**4,132 mm**
Max. dumping height	**2,742 mm**
Max. digging reach	**4,610 mm**
Transport length	**4,159 mm**
Width	**1,550 mm**
Height	**2,560 mm**
Bucket capacity	**0.10 m³**
Bucket width	**480 mm**
Bucket digging force	**20 kN**
Hydraulic pump	**piston Le-HydrauliX**
Working pressure	**24.3 MPa**
Tracks	**rubber 300 mm (steel optional)**
Travel speed	**2.0 / 4.0 km/h**
Two-speed travel	**standard**
Fuel tank	**35 L**

Sales, service and warranty: AVELKOR Sp. z o.o. (Poland)

ul. Jarzębinowa 10, 11-034 Stawiguda, Poland · +48 511 956 011 · info@aveltor.pl · aveltor.pl/en/herestrong.html

Technical data according to the manufacturer. Net prices valid on the print date. The manufacturer may change equipment and specifications.